

CORPORATE VISION

To be South East Asia's foremost distributor of quality bolts & nuts.

CORPORATE MISSION

Consistently providing the best products & services, and be proactive to the needs of our customers.

CORPORATE PHILOSOPHY


We earn customer loyalty by consistently supplying high standard bolts & nuts which strictly adhere to their required specification, time schedule and our policy to render our best efforts to serve our customers.


OUR CORE VALUES

- O Uncompromising in the quality of products we distribute
- Committed to excellent customer service
- To remain united in teamwork for growth
- O Pursue corporate progress for the good of all

WE PLEDGE THAT

We will continue to accord our Customers our top priority, and, even as we grow in partnership, it will remain our responsibility to Better ourselves continually and Never to be complacent.







OC DEPARTMENT

CBN Quality Control Laboratory is committed to provide reliable, consistent and efficient quality testing services, with continued improvements in the standards of quality for the customer's satisfaction.


Our mechanical tests are in accordance to ISO testing standard and all documents are stored for any future reference. With the set up of a Quality Control Laboratory, customers can be assured that all products supplied from CBN are manufactured and checked to the specified quality specifications.

Our testing capabilities include:

Mechanical properties

- · Tensile Strength
- · Yield Strenght
- · Proof Load
- · Hardness (Core and Surfaces)

CBN, 32 years of reliability, sincerity and confidence since 1976.



wigh Tensile













FIOT (JIS B1186) - High Strength Friction Grip Bolt

Features:

Equivalent to : BS4395 Pt.2 (Higher Grade)

ASTM A490 DIN6914 AS1252

Stock Range

Diameter : 12mm - 36mm Length : 30mm - 300mm

Brands : NSB, JH

Principal Agent for NSB, JH



High Strength Tension Control (Tor - Shear Type) Bolts & Nuts

Features:

- Grade SIOT (JSS-11-09)
- · Correct torque made easy
- Complete with washer
- Available in Anti-Rust series

Stock Range

Diameter : 16mm - 30mm Length : 35mm - 200mm

Brands : NSB, JH

· Principal Agent for NSB, JH



Shear Connector / Ferrules

Features:

 Conforming to: BS5400 JIS B1198 AWS

Stock Range

Diameter : 13mm - 22mm Length : 50mm - 180mm

· Brand : JH



SHEAR WRENCH For High Strength Tension Control Bolts

Features:

- Offer greater efficiency in operation for fastening Bolts of Torque Shear type.
- Models available
 - H-series
- H-242 EZ
- M-series
- M-222 EZ /: \$-60EZA, \$-90EZ, \$-110EZ, \$-210EZ, \$-80EZ S-series
- Manual Series: S-20HA, S-24HA

Brand

: TONE (Japan)



SIMPLE TORQON - Electric Torque Control Wrench

Features:


- Electric Torque Control Wrench
- Offer high accuracy & easy operation for fastening hexagon bolts.
- Torque control function on both directions.
- Models available
 - SR32E, SR52E, SR72E, SR122E, SR212E.
- Brand

: TONE (Japan)



Bolt Tension Calibrator

- For easy, on-site measurement of bolt tension in structural measurement.
- Capacity
 - Model MS
- : 90,000 lbs of bolt tension : 110,000 lbs of bolt tension : 170,000 lbs of bolt tension
- Model M Model H
- Brand
- : Skidmore-Wilhelm (USA)



High Tensile Hexagon Head Bolts & Nuts

Features:

- Metric & Inches series
- DIN 931 / 933 (Grade 8.8 / 10.9 Strength)
- BS 1768 (Grade 5 / Grade 8 Strength)

Stock Range

Diameter Length

: 4mm - 56mm : 8mm - 400mm

Diameter Length

: 1/4 " - 2" : 1" - 20"

 Brand etc.

: JH, CW, SFC, KEF,



High Strength Structural Hexagon Head Bolts & Nuts To ASTM A325

Features:

- Equivalent to : BS 4395 Pt.1
- Suitable for structural bolting.
- Sizes in inches (ASTM standard)
- Optional

Flat Harden and / or

Load Indicating Washers

Stock Range

Diameter Length

: 1/2" - 1 1/4" : 1" - 9"

Brand

: JH, SFC, etc.



Komatsu / Heavy Duty Hexagon Head Bolts

- Metric (Grade 10 strength) & Inches (Grade A9) series.
- Alloy steel to 170,000 psi tensile strength
- OEM equivalent (Caterpillar, Komatsu, etc.)
- Segmented Bolts & Nuts also available upon request.



High Tensile Products Hexagonal Socket Head Cap Screws

Features:

· High quality to International Standard

Metric & Inches series

DIN912

BS2470

Stock Range Diameter

Length

: 3mm - 42mm : 5mm - 300mm

Diameter Length

: 1/8" - 1 1/2" : 1/4" - 12"



Hexagonal Socket Countersunk Head Screws

Features:

· High quality to International Standards

Metric & Inches series

DIN7991

BS2470

Stock Range

Diameter Length

: 3mm - 24mm : 6mm - 100mm

Diameter

Length

: 3/16" - 1" : 1/4" - 4"

Hexagonal Socket Head Set Screws



High quality to International Standards.

Ball Plungers

DIN916

BS2470

Stock Range

Diameter

: 3mm - 24mm : 3mm - 60mm

Length

Diameter

Length

: 1/8" - 1" : 1/8" - 3"





Wrenches for Hexagonal Head Socket Screws

Features:

- · Long & Short Arm
- · Individual size or set (Assorted sizes)
- Metric & Inches series
- DIN 911
- BS2470
- Stock Range : 2mm 27mm I/16" - 1"



Hexagonal Socket Head Shoulder Screws

Features:

- DIN 9841
- Stock Range Diameter Length





Fully Threaded Studs

Features:

- Available in Mild Steel, High Tensile (S45C) & Alloy Steel (B7) type.
- · May be cut to length required.
- · Stock Range

Diameter : 6mm - 42mm

Length : 2 meter


Diameter : 1/4" - 2" Length : 6 feet



Special Bolts

Features:

- Holding-Down Bolt
- Sag Rod
- U-Bolt
- A193 B7 Stud Bolt c/w A194 2H Nut
- A320 Stud Bolt





Special Nuts

Features:

- Lock Nuts Nylon Inserted type - DIN985
- Flange Nuts
- Coupling Nuts BN
- Dome Cap Nuts
- Spiral Locked Nuts
- Wing Nuts
- High Nuts
- Slotted / Castle Nuts
- Large Hexagon Nut : 39mm - 100mm



Special Washers

CE Features:

- Plain Round Washers: Zinc or Nickel Plated / Hardened, etc.
- Spring Washers
- Load Indicating Washers / D.T.I
- General / Higher Grade
- Wave Washers
- Overlapped Locked Washers (Internal & External)
- Toothed Washers (Internal & External)
- Tapered Washers





Anchor Bolts / Expansion Bolts / Drop In Anchor

Features:

- Set / Stud Anchor c/w Nut & Washers and "Drop-in Anchor"
- Reliable anchoring as expansion is effected by tightening of nut
- Fast in-place fastening process.



Hollow pin / Cotter pin / Dowel pin

Features:

Hollow pin

Chamfered at both ends for easy installation & removal. Individual sizes or Assortmen

Stock Range 12mm


Cotter pin • BS1574

Single size or Assortments. Stock Range : 1/16" - 3/8" Stock Range

Dowel pin DIN 6325

Stock Range Diameter

Length





Circlips - External, Internal & E Types

Features:

- High quality to International Standards.
- Individual size or Assortments

: A004 - A260 Stock Range

B005 - B320 E001.2 - E024

Brand : Anderton, ALPA



Grease Nipples

Features:

- Available in SAE, BSP, PT, NPT, met inches etc, sizes.
- · Clean lubrication with ball in front
- Nickel plated
- Brand SK (Japan)





Grease Gun / Oil Sunction Guns

Features:

- Normal & Air Type
- Accessories include Grease Hoses, couplers, etc.

 CBU
- Brand
- : Umeta (Germany



Hydraulic Jack



- Bottle type Kayaba (Japan)
 Stock Range . . . 5 Tons 50 Tons
- Also available in Weber (Germany) Stock Range . 1.5 Tons - 100 Tons







Coated Bolts & Nuts

Features:

- · Available in customer's request coating :
- Zinc Electroplated (JIS H8610-1974)
- Hot-Dip Galvanized (BS EN ISO 1461-1999)
- Mechanical Zinc Deposited Coating
- Fluorocarbon Coated



Bolts & Nuts To BS916: 1953 (Mild Steel)

Features:

- ISO Metric series to Grade 4.6; DIN 558 / 601
- · Self colour or zinc galvanized / HDG
- Stock Range 50 52mm 52mm Length 12mm 300mm

Diameter : 1/4" - 3" Length : 1/2" - 24"



Carriage Bolts & Nuts

- ANSI B.18.5 1953
- Available in Grade 2 or Grade 5 (H.T)
- · Complete with square or hex nuts.



inless Sign









Stainless Steel Hexagon Head Bolts & Nuts

Features:

- Metric & Inches series
- JIS SUS304 (AISI304, BS304, S15/16)
- JIS SUS316 (AISI316, BS316, S16/49)
- DIN 931 / DIN 933 / DIN 934 / ANSI B18.2.1 / ANSI B18.2.2 (UNC)
- Stock Range

Diameter: 3mm - 42mm Length: 8mm - 300mm

Diameter : 3/16" - 2" Length : 1/2" - 20"



Stainless Steel Hexagonal Socket Cap Screws & Set Screws / Stainless Steel Hexagonal Socket Countersunk Head Screws & Button Head Screws

Features:

- Metric & Inches series
- JIS SUS 304
- JIS SUS 316
- JIS B1176, DIN 912, DIN 7991, ISO 7380

Stock Range
Diameter: 2mm - 24mm
Length: 4mm - 100mm

Diameter : 1/8" - 1" Length : 3/8" - 3" Length



Stainless Steel Machine Screws

Features:

- Pan Head / Flat Head (CSK) / Round Head
- Philips / Slotted
- Metric & Inches series
- JIS SUS 304
- JIS SUS 316
- DIN 965, DIN 7985
- Stock Range

Diameter : 2mm - 12mm Length : 4mm - 60mm

Diameter : 3/16" - 1/2" Length : 3/8" - 4"



Stainless Steel Self - Tapping Screws

Features:

- Pan Head / Flat Head (CS
- Philips type
- JIS SUS 304
- JIS SUS 316
- DIN 7981, DIN 7982





Stainless Steel Self - Drilling Screws

Features:

- SUS 304
- SUS 316
- SUS 410
- **DIN 7504**



- Pan Head / Flat Head (CSK) / Hexagon Washer Head / Hexagon Flange Washer Head
- Heat treatment made hardened thus increase drilling performance
- Optional
- Attach with Rubber Washer / Bonded Washer
- Stock Range : Regular sizes range



Stainless Steel Anchor Bolts / Expansion Bolts



- JIS SUS 304
- JIS SUS 316
- Providing a secure, heavy-duty anchorage for fixings to concrete
- Give complete support in shear for a stronger fastening against dynamic side loads
- Quick & easy installation



Stainless Steel Spring (Hollow) Pins / Cotter (Split) Pins

Features:

Hollow Pin

Chamfered at both ends for easy installation & removal

 Stock Range : 1.5mm - 12mm 1/16" - 1/2"

Cotter Pin

BS1574, 1958

Stock Range : 1/16" - 3/8"



Stainless Steel Fittings

Features:

- Standard type: Elbow 90°, Union, Tee, Nipple, Socket, Elbow 45°, End Cap, Square Plug.
- Reducing type: Reducing Bush, Reducing Socket, Reducing Tee, Reducing Nipple, Reducing Elbow 90°
- JIS SUS 304
- · Available in BSP Thread
- Pressure to 150 psi
- Stock Range : 1/4" 4"



Stainless Steel Flanges

- Flat Face, Raised Face, Blind Raised Face & Slip On Raised Face
- JIS 5K, JIS 10K, PN10, PN16 & ANSI 150 lb.
- JIS SUS 304
- Stock Range : 1/2" 14"



Stainless Steel Special Bolts

Features:

Carriage Bolts DIN 603

- JIS SUS 304
- JIS SUS 316
- Circular head with a low rounded top surface and integrally formed square neck under the head

 Stock Range ... Regular sizes range

U-Bolt

JIS SUS 304 JIS SUS 316

To support pipes / rods Stock Range : 1/2" - 8"



Stainless Steel Special Nuts

Features:

- Nylon Insert Lock Nuts
- Domed Cap Nuts
- Wing Nuts (
- JIS SUS 304
- JIS SUS 316
- DIN 985, DIN 1587, DIN 315



Stainless Steel Washers

- Flat Washers
- Spring Washers
- JIS SUS 304
- JIS SUS 316
- DIN 125, DIN 127
- Toothed Washers (Internal & External)
- Tapered Washers



Stainless Steel Fully Threaded Studs

Features:

- JIS*SUS 304
- JIS SUS 316
- DIN 975
- May be cut to length required

Stock Range :

Diameter

: 3mm- 30 mm

Length

: I meter / 2 meter

Diameter

: 1/4" - 1 1/2"

Length

: 6 feet



Stainless Steel Circlips - External, Internal & E Type

Features:

 High quality to all International Standards

Stock Range





Stainless Steel Grease Nipples

Features:

- · Clean lubrication with ball in front
- 45°, 90°, straight type, pin type & button type.
- · Available in BSP standard

· Stock Range : Regular sizes range

Brand : SK Brand (Japan)



sinean, so















Engineering Products

Drills

Features:

- Product
 - Straight Shank Jobber Drill (Standard, Long & Extra Length Drill) - Morse Taper Shank Drills

 - 1/2" Diameter Parallel Shank Drills
 - Centre Drills
- Material
 - HSS (High Speed Steel) HSS 8% Cobalt

 - HSS + TIN Coating Solid Carbide (MG)
- : Metric & Inches Size
- Brand :
 - Presto
 - Dormer
 - Garryson
 - Sutton

(Australia)



Milling Cutters

Features:

- Product

 - Slot Drill 2 Flutes Slot Drill Ballnosed 2 Flutes
 - Tri Cutter 3 Flutes
 - End Mills Multi Flutes
 - Ripping Cutters
- Material

 - HSS & HSS Cobalt HSSCo with TiCN Coating
 - Solid Carbide (MG)
 - Solid Carbide with TiALN Coating
 - Rapide Coated
 - (High Speed Machinery)
- Brand :

 - Presto (U.K)
 Garryson (U.K)
 Sutton (Australia)



Threadlocking Adhesive, Anti-Seize Lubricating Compound & Cutting Oil

- Provide speedy assembly
 - Prevent rust & corrosion
 - Prevent part loosening
 - Prevent wear & tear & galling
 - Assure removability
- Brand
 - SAF-T-LOK
 - SAF-T-EZE
 - Belling



Engineering Products

Hand & Machine Tap

Features:

- Product
 - Short Machine Taps (Spiral Point & Spiral Flute) - Hand Taps

 - Fluteless Roll Taps
 - Screw Extractors
- Material
 - HSS
 - HSSE
 - HSCo TiALN Coating
- Size : Metric & Inches
- Brand

 - Presto (U.K)
 Dormer (U.K)
 Sutton (Australia)



Circular Split Dies, Hexagon Dies & Tap & Dies Set

Features:

- Product
 - Circular Split Dies
 - Hexagon Dienuts
 - Tap & Die Sets
- Material
 - Carbon Steel
 - HSS
- Size : Metric & Inches
- Brand

 - Presto (U.K) Triangle(U.K)



Hacksaw Blades (Eclipse)

- - Hacksaw Blades (Eclipse)
 - High performance
 - Shatter proof blade
- Material
 - All Hard
 - Bi Metal
- Size : 18 TPI
 - : 24 TPI : 32 TPI
- Brand
 - Eclipse (U.K)



Engineering Products

Reamers

Features:

- Product
 - Machine Reamers
 - Machine Chucking Reamers

 - Hand & Taper Pin Reamers Machine Taper Bridge Reamers Adjustable Hand Reamers

 - Countersinks
 - Corner Rounding Cutter
- Material : HSSCo
- : Metric & Inches Size
- **Brand**
 - T & J (U.K) Dormer (U.K)



Tungsten Carbide Burrs & Burrs Kit

Features:

Product Cylinder, Cylinder with End, Ballnosed, Cylinder Ball, Oval, Ball Nosed Tree, Tree, Flame, Countersink 60°, Countersink 90°, Ballnosed Cone, Cone, Inverted Cone, Rim.

Material: Tungsten Carbide

: Standard, Diamond, Type Chipbreak, Aluminium.

Brand : Garryson (U.K)



Abrasives

Features:

- Product

 - Flap Disc.Flap Wheels
 - Blocks
- Material
 - Aluminium Oxide
 - Zirconium
 - Zirc+
- : G40, G60, G80, G100, Grifts

G120, G150, G180,

G240, G320

