



V9944

V9944. Braided packing with glass yarn. The packing is impregnated with PTFE and lubricants silicon free. Available in the style V9900 without impregnation.

Packing suitable for general uses in dynamic services.

Technical Sheet

Composition

Features

Applications

sezione mm	sezione inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3	37468	1	2.2	61.7	203	61.7	91.9
4	-	1	2.2	34.7	114	34.7	51.7
5	40968	1	2.2	22.2	73	22.2	33.1
6	-	2.5	5.5	38.6	127	15.4	23
6.5	37346	2.5	5.5	32.9	108	13.1	19.6
8	41029	2.5	5.5	21.7	71	8.7	12.9
9.5	37470	2.5	5.5	15.4	50	6.2	9.2
10	-	2.5	5.5	13.9	46	5.6	8.3
11	41090	2.5	5.5	11.5	38	4.6	6.8
12	-	2.5	5.5	9.6	32	3.9	5.7
12.7	37287	2.5	5.5	8.6	28	3.4	5.1
14	41152	5	11	14.2	46	2.8	4.2
16	37472	5	11	10.9	36	2.2	3.2
17.5	41213	5	11	9.1	30	1.8	2.7
18	-	5	11	8.6	28	1.7	2.6
19	37348	5	11	7.7	25	1.5	2.3
22	37474	5	11	5.7	19	1.1	1.7
25.5	1	5	11	4.3	14	0.9	1.3